

*Technical Data Sheet***20540****ELASTICIZZANTE****DESCRIPTION OF THE PRODUCT:**

Solution of oxidised saturated polyester resin.

FIELDS OF APPLICATION:

Flexibiliser for two-component polyurethane products. Permanently increases the elasticity of the paint film. Increases resistance to mechanical stress (bending or impact) even at low temperatures. It does not change the chemical and lightfastness characteristics of the products in which it is used.

PRODUCT PREPARATION:

Add 5 to 15% in component A of two-component polyurethane systems.

Shake thoroughly.

For larger addition quantities, please consult the Research and Development Laboratory of Caldart Vernici srl.

PRODUCT SPECIFICATIONS:

TYPE OF PRODUCT	: Resin solution
MASS COLOUR	Transparent
SPECIFIC WEIGHT	1.050 kg/Lt (± 0.020)
DRY RESIDUAL	: 64,00 % (± 2)

SAFETY REGULATIONS:

Strict adherence to the labelling and safety data sheet is required.

STABILITY IN STORAGE:

24 months in sealed containers not exposed to the sun (max. temp. 30°C).

The data and information contained herein are the result of our experience and thorough laboratory tests and trials. However, as the painting process is a series of operations that are beyond our control, they do not constitute, in any way, any form of guarantee on the final performance of the cycle itself.

Rev.: 05/25