

Data sheet

D.030

ANTISILICONE

 RECORD
ITALIAN CAR REFINISHING

FIELD OF APPLICATION:

Product formulated with a mixture of solvents suitable for removing any traces of pollutants from surfaces such as waxes, polishing preparations, silicones, grease.

Specific use is in auto body shops and industry for cleaning sanded primers before final painting.

Product complies with Directive 2004/42/EC-IIIB(a) maximum VOC content: 850 g/l

APPLICATION METHODS:

Apply a generous amount of D.030 cleaner to a wet cloth.

Clean surfaces by rubbing, before and after sanding.

Then dry the product thoroughly with a clean cloth.

Do not use dirty cloths and change them often.

Do not let the product dry by solvent evaporation, otherwise the removal of contaminants would be null.

For more technical information or for specific cycles and/or special applications please consult our TECHNICAL ASSISTANCE.

FOR PROFESSIONAL USE ONLY.

SAFETY REGULATIONS:

Strictly follow the instructions on the labeling and in the safety data sheet.

STORAGE STABILITY:

In unopened and sealed packages, kept at a temperature of +5 to +30 °C.

The data and information contained in this sheet are the result of our experience and accurate laboratory tests. However, since the painting process represents a set of operations that are beyond our control, they do not therefore guarantee, in any way, the final performance of the cycle.

Rev.: 03/22