

Technical Data Sheet

DW030

ANTISILICONE ALL'ACQUA

RECORD
ITALIAN CAR REFINISHING

APPLICATIONS:

Product formulated with a blend of polar solvents suitable for removing any traces of contaminants such as waxes, polishing compounds, silicones and grease from surfaces.

It is specifically designed for use in body shops and industry for cleaning sanded undercoat-primers prior to final varnishing.

Product compliant with Directive 2004/42/EC-IIb(a), maximum VOC content < 420 g/l

METHOD OF APPLICATION:

Apply a generous amount of DW030 detergent to a damp cloth.

Clean the surfaces by rubbing, both before and after sanding.

Then dry the surface thoroughly with a clean cloth.

Do not use dirty cloths and change them frequently.

Do not allow the product to dry through solvent evaporation, otherwise the removal of contaminants will be ineffective.

For further technical information or for specific cycles and/or particular applications, please consult our TECHNICAL SUPPORT.

FOR PROFESSIONAL USE ONLY.

SAFETY PRECAUTIONS:

Strictly adhere to the instructions on the label and in the safety data sheet.

STORAGE STABILITY:

In intact, sealed packages, stored at a temperature between +5 and +30 °C.

The data and information contained in this sheet are based on our experience and on accurate laboratory tests. However, as the varnishing process involves a series of operations beyond our control, they do not in any way constitute a guarantee of the final performance of the process itself.

Rev. No. 1 of 15/12/25