

*Data sheet***Z.010****ANTI-GRAFFITI ADDITIVE****NATURE OF PRODUCT:**

Anti-graffiti additive (2% - 4%) for finishing colors, obtained from **211** or **7H1** series enamel.

FIELD OF APPLICATION:

For public transportation and industrial vehicles, or where anti-graffiti treatment is required.

PREPARATION OF THE SUBSTRATE:

As per the data sheet of the product to be activated.

PREPARATION OF THE PRODUCT:

Comp. A :	Enamels Series 211 / 7H1	1000 ml
Anti-graffiti additive:	Z.010	20 - 40 ml

Mix carefully (possibly with a stirrer) making sure the additive is evenly mixed.

For subsequent preparation of enamels, and application of glazes, follow the recommended directions in the relevant data sheets.

NOTE:

The anti-graffiti treatment is effective only when the film is completely dried and has reached the maximum level of its chemical resistances.

If there is a need for **repainting**, careful sanding of the surface and subsequent degreasing is essential.

Anti-graffiti power is subject to loss in effectiveness over time, depending on the wear and tear of the product it is added to.

SAFETY REGULATIONS:

Strictly follow the instructions on the labeling and in the safety data sheet.

STORAGE CONDITIONS:

The storage room must be dry and with a temperature between +10 °C and +35 °C.

The data and information contained in this sheet are the result of our experience and accurate laboratory tests. However, since the painting process represents a set of operations that are beyond our control, they do not therefore guarantee, in any way, the final performance of the cycle.

Rev.: 12/22