

Data sheet

Z.020

ANTI-CRACKING LEVELING ADDITIVE

NATURE AND PRODUCT FEATURES:

Modified silicone polymer solution.

FIELD OF APPLICATION:

The use of this additive increases substrate wettability, levels the film and features surface hardness and slip effect, as well as having a moderate anti-cracking effect.

PREPARATION OF THE PRODUCT:

Comp. A :	Enamels and/or paints	1000 ml	1000 gr
Leveling Additive :	Z.020	10 - 20 - 30 ⁽¹⁾ ml	10 - 20 - 30 ⁽¹⁾ gr

Mix carefully (possibly with a stirrer) making sure the additive is evenly mixed.

For subsequent preparation of enamels, and application of glazes, follow the recommended directions in the relevant data sheets.

⁽¹⁾ In the case of two-component finishes.

NOTE:

Additions above the recommended amount do not lead to significant improvement in the above properties; on the other hand, they may cause film glazing.

SAFETY REGULATIONS:

Strictly follow the instructions on the labeling and in the safety data sheet.

STORAGE CONDITIONS:

The storage room must be dry and with a temperature between +10 °C and +35 °C.

The data and information contained in this sheet are the result of our experience and accurate laboratory tests. However, since the painting process represents a set of operations that are beyond our control, they do not therefore guarantee, in any way, the final performance of the cycle.

Rev.: 10/22