

*Data sheet***Z.040****ANTI-SCRATCH ADDITIVE****NATURE OF PRODUCT:**

Anti-scratch additive based on modified silicone resins.

**FIELD OF APPLICATION:**

For public transportation and industrial vehicles, or where high resistance to scratching and surface wear is required.

Compatible with the following resins: **K.734 - K.719 - K.712 - K.713 - K.224 - K.732 - K.714 - 704.TIX40.**

**PREPARATION OF THE PRODUCT:**

Comp. A :	<b>Enamels</b>	1000 ml
Anti-scratch additive:	<b>Z.040</b>	10 - 30 ml

Mix carefully (possibly with a stirrer) making sure the additive is evenly mixed.

For subsequent preparation of enamels, and their application, follow the recommended directions in the relevant data sheets.

**NOTE:**

If there is a need for repainting, careful sanding of the surface and subsequent degreasing is essential.

**SAFETY REGULATIONS:**

Strictly follow the instructions on the labeling and in the safety data sheet.

**STORAGE CONDITIONS:**

The storage room must be dry and with a temperature between +5 °C and +30 °C.

*The data and information contained in this sheet are the result of our experience and accurate laboratory tests. However, since the painting process represents a set of operations that are beyond our control, they do not therefore guarantee, in any way, the final performance of the cycle.*

**Rev.: 12/22**