

*Data sheet***Z.050****ANTI-CRACKING LEVELING ADDITIVE****NATURE OF PRODUCT:**

Additive based on compounds derived from quaternary ammonium.

The addition of the additive in solvent-based coatings decreases their electrical resistance, allowing for optimized application and "winding" effectiveness in applications with electrostatic systems.

**FIELD OF APPLICATION:**

Can be used in all solvent-based paint products.

**PREPARATION OF THE PRODUCT:****Component A**

Two-component enamels and paints: 100 parts by weight

Single-component enamels and/or paints: 100 parts by weight

Mix carefully, making sure the additive is evenly mixed.

For subsequent preparation of enamels, and their application, follow the recommended directions in the relevant data sheets.

**Electrostatic additive Z.050**

1 - 2 parts by weight

0,5 - 1 part by weight

**SAFETY REGULATIONS:**

Strictly follow the instructions on the labeling and in the safety data sheet.

**STORAGE CONDITIONS:**

The storage room must be dry and with a temperature between +10 °C and +35 °C.

*The data and information contained in this sheet are the result of our experience and accurate laboratory test. However, since the painting process represents a set of operations that are beyond our control, they do not therefore guarantee, in any way, the final performance of the cycle.*

**Rev.: 10/22**