

*Data sheet***Z.080****RETARDANT ADDITIVE FOR WB PRODUCTS****NATURE AND PRODUCT FEATURES:**

Mixture of high-boiling solvents.

**FIELD OF APPLICATION:**

Retardant for water-based 1K enamels and/or primers such as our **KW4xx series** and for 2K acrylics such as our **KW7xx series**, including our finishing paints **701W00020** and **704W0004**.

**PREPARATION OF THE PRODUCT:**

Comp. A :	<b>Enamels 1K</b>	1000 gr	
Or	<b>Enamels 2K</b>	1000 gr	
Retardant additive:	<b>Z.080</b>	2 - 3 gr	2 - 5 gr

Mix carefully (**possibly with a stirrer**) making sure the additive is evenly mixed.

**NOTE:**

Not suitable for epoxy systems.

**STORAGE CONDITIONS:**

The storage room must be dry and with a temperature between +5 °C and +30 °C.

**SAFETY REGULATIONS:**

Strictly follow the instructions on the labeling and in the safety data sheet.

*The data and information contained in this sheet are the result of our experience and accurate laboratory test. However, since the painting process represents a set of operations that are beyond our control, they do not therefore guarantee, in any way, the final performance of the cycle.*

**Rev.: 12/22**