

*Data sheet***Z.430****ACCELERATOR ADDITIVE FOR R.E. ENAMELS.****NATURE AND PRODUCT FEATURES:**

Accelerator for synthetic and fast-drying resins.

**FIELD OF APPLICATION:**

For converters and fast-drying finished products, such as our **411 - 421 - 431 - 433 - 631 - 624 - 644** series.

**PREPARATION OF THE PRODUCT:**

Comp. A :	<b>Converter or finished product</b>	1000 gr
Accelerating additive:	<b>Z.430</b>	10 - 20 gr

Mix carefully (possibly with a stirrer) making sure the additive is evenly mixed.

For subsequent preparation of enamels, follow the directions on the relevant data sheets.

**NOTE:**

Do not exceed the recommended dosage.

Do not use on **490 - 494** series primers.

The addition of the accelerating additive **Z.430** in brush-on synthetic resins promotes the formation of skin in the can, so it is recommended to use the additivated product within **1 - 2 weeks**.

**STORAGE CONDITIONS:**

The storage room must be dry and with a temperature between +5 °C and +30 °C.

**SAFETY REGULATIONS:**

Strictly follow the instructions on the labeling and in the safety data sheet.

*The data and information contained in this sheet are the result of our experience and accurate laboratory test. However, since the painting process represents a set of operations that are beyond our control, they do not therefore guarantee, in any way, the final performance of the cycle.*

**Rev.: 12/22**