

Data sheet

TP Series

UNIVERSAL CONCENTRATED PASTES SOLVENT-BASED



Always close
cans after use

NATURE AND PRODUCT FEATURES:

Concentrated pastes based on synthetic resin and polymeric wetting agent, with broad compatibility with most common solvent-based paint products.

All listed pastes are manufactured from nonheavy metal-based raw materials (*EN 71/3*).

FIELD OF APPLICATION:

Universal use in solvent-based paint products.

Selected specifically for single-component and two-component coating products used in the decoration and protection of plastic eyewear (CA, CP, PA).

Can be used in specific single-component baked systems, also in the eyewear industry (in this case, please consult *Vernici Caldart R&D Laboratory*).

They can be used with most of our *Industry List K. series* converters and, particularly suitable, with 2K polyurethane or acrylic resins and with R.E., nitro or base-coat single-components.

PREPARATION OF THE PRODUCT:

Pastes should always be stirred before use, and dosed as follows:

Single-component *plastic paints* : up to 15% MAX

Two-component *plastic paints* : up to 25% MAX

Single-component *metal baked paints* : up to 20% MAX

Industry *K series* converters: follow the formulation reported by *Colortech* related to the required color

SAFETY REGULATIONS:

Strictly follow the instructions on the labeling and in the safety data sheet.

STORAGE CONDITIONS:

Store indoors at a temperature below 30 °C. Avoid direct exposure to the sun.

Close containers thoroughly immediately after use. Always shake well before use.

The data and information contained in this sheet are the result of our experience and accurate laboratory tests. However, since the painting process represents a set of operations that are beyond our control, they do not therefore guarantee, in any way, the final performance of the cycle.

Rev.: 12/22